# VpCI®-309 Pouch

# Corrosion Inhibiting VpCI® Pouch for Ferrous Metals



### PRODUCT DESCRIPTION

VpCl-309 Pouch contains a Vapor phase Corrosion Inhibitor (VpCl) powder for corrosion protection of ferrous metals in recessed areas, interior cavities, and voids. The pouches are constructed from breathable \*Tyvek®, which allows the VpCl molecules to be emitted through the membrane and form a molecular layer on metal surfaces providing corrosion protection.

VpCI-309 pouch is easy to use: there are no chemical concentrations to calculate and no need for special equipment for application; just determine the number of pouches required per unit space. VpCI-309 Pouches provide a clean method for corrosion protection.

VpCI-309 Pouch provides an extremely efficient dry method to protect metals within an enclosed space. The VpCI vaporizes and adsorbs on all metal surfaces reaching all exposed areas including recessed sections and interior cavities.

VpCI-309 Pouches are available as individually cut pouches and each pouch protects up to 1 m<sup>3</sup>. Custom sizes and constructions are also available.

#### **FEATURES**

- Does not contain silicates, phosphates, nitrites, or heavy metals
- Provides up to 24 months of continuous protection
- Vapor phase inhibiting action protects inaccessible and recessed surfaces
- If the VpCl layer is disturbed by moisture or opening the enclosed space, the layer is replenished by continuous vapor redeposition
- Protected products can be shipped to customers without removing protective VpCl film
- Prevents further corrosion of pre-coated and painted surfaces
- Clean and easy to use
- · Provides protection to ferrous metals only
- LD<sub>50</sub> ORAL: 2100mg/kg of body weight (rat)

#### **TYPICAL APPLICATIONS**

- Tubular structures, pipes, vessels, and turbines
- Internal surfaces of compressors, turbines, engines, tanks, boilers, and heat exchangers
- Dry lay-up of closed circuit cooling systems
- Equipment protection after hydrostatic testing
- Parts, components, and completed assemblies during shipping and storage

#### **METALS PROTECTED**

- Carbon steel
- Stainless steel
- Aluminum

# **METHOD OF APPLICATION**

Determine the number of pouches required based upon the volume of space needing protection. Each pouch protects up to 1m³ (35 ft³). Evenly distribute pouches throughout the space and close or seal enclosure.



#### **TYPICAL PROPERTIES**

Form: Tyvek breathable pouch Appearance: White with green printing

Dimensions: Each pouch is 6" W x 10" L x 0.5" H

 $(15.3cm \times 25.4cm \times 1.3cm)$ 

#### **PACKAGING AND STORAGE**

VpCl-309 Pouches are available as 50 units per carton. Do not store in conditions above 150°F (65°C). Close cartons between uses. The shelf life of unopened cartons of VpCl-309 Pouches is up to 24 months.

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE
INFORMATION

## **LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defection. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be naid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. We representation or recommendation not contained herein shall have any force or effort unless in a written document.

representation or recommendation not contained herein shall have any force or effect unless in a written documer signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com Internet http://www.CortecVCI.com

printed on recycled paper

100% post consumer
Revised 2/1/11. Cortec Corporation 2009-2011. All rights reserved. Supersedes: 10/09/09.
VpCI® is a trademark of Cortec Corporation.
© 2011, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited.
ISO accreditation applies to Cortec's processes only.

Distributed by: