



HIGH PERFORMANCE VpCI® PACKAGING

VpCI®-357

PRODUCT DESCRIPTION

VpCI-357 provides multimetal vapor corrosion inhibitor protection to flexible packaging materials. This solution is used to produce a high-quality finished product which resembles the original paper surface and finish. This unique combination of organic vapor phase corrosion inhibitors is applied directly to paper, chipboard, corrugated and foam substrates using conventional coating equipment. VpCI-357 is available as a water-based (VpCI-357 W) or as a water/ethanol-based (VpCI-357 AHS) solution. This high-technology product provides protection to many metals including steel, galvanized steel, copper, brass, silver, solder, and aluminum.

APPLICATION

VpCI-357 is applied directly to the substrate with most common roll coaters such as gravure, air knife, or reverse roll. Drying temperatures are 180-200°F (82-93°C). However, in some instances, drying may not be necessary as in a case of corrugated or chipboard processes. The minimum coating weight for all packaging material is 2 pounds dry VpCI per 3,000 sq.ft.ream (3.2 g/m²). A coating weight of 3-5 pounds per ream (4.9-8.1 g/m²) is recommended to achieve maximum shelf-life or when additional production procedures, such as lamination, are required. In addition to kraft paper, VpCI-357 is suitable for other flexible packaging materials such as corrugated, chipboard, cardboard and laminated/reinforced papers, foams, etc.

PHYSICAL PROPERTIES VpCI-357 AHS

Appearance	Clear amber liquid
Non-volatile Content	40-45%
pH	8.5-9.0 (Neat)
Density	8.4-8.5 lb/gal (1.01-1.02 kg/l)

PHYSICAL PROPERTIES VpCI-357W

Appearance	Clear amber liquid
Non-volatile Content	23-28%
pH	7.8-8.2 (Neat)
Density	8.7-8.9 lb/gal (1.04-1.07 kg/l)

PHYSICAL PROPERTIES VpCI 357A

Appearance	Clear amber liquid
Non-volatile content	25-30%
pH	7.9-8.4 (Neat)
Density	8.2 - 8.4 (wpg)

PACKAGING AND STORAGE

VpCI-357 available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes, and bulk. The shelf life of VpCI-357 is 24+ months.

Keep away from the heat and opened flame sources. Store in temperatures >10°C.

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR
MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Distributed by:



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer
Revised 1/14/13. ©Cortec Corporation 2003-2013. Supersedes: 5/2/11.
2013, Cortec Corporation. All rights reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.